

HYCON HH35 BREAKER

ANTI-VIBRATION HANDLES

HIGHEST PERFORMING HANDHELD BREAKER



PRODUCT FEATURES

HYCON HH35 is exceptionally strong in coping with all jobs requiring extreme power. It hits more than twice as hard as the HH20 and outperforms any other 45 kg breaker in the market – no matter if pneumatic or hydraulic. The breaker has an extra accumulator, which adds even more power.

The HH35 is designed for breaking reinforced concrete and

asphalt, ramming jobs, etc. It comes with the HYCON vibration-reduced handle as standard.

It is mainly used in contracting, demolition, and road work industries. The standard tool size is hex 32 x 160 mm. The breaker can be connected to the HYCON power packs and other hydraulic power sources.

HYDRAULIC BREAKER HH35

	CE 28x160	CE 32x152	CE 32x160
Item no.	1010135	1010035	1010235
Weight [kg / lbs]	29.4 / 64.8	29.4 / 64.8	29.4 / 64.8
Oil flow [LPM / GPM]	30 - 40 / 8 - 10	30 - 40 / 8 - 10	30 - 40 / 8 - 10
Working pressure [bar / psi]	130 / 1885	130 / 1885	130 / 1885
Max pressure [bar / psi]	160 / 2320	160 / 2320	160 / 2320
Tool shank HEX [mm] (optional)	28 x 160	32 x 152	32 x 160
Blow frequency [Hz]	1100 - 1440	1100 - 1440	1100 - 1440
Blow energy [joule]	130	130	130
Sound power level L _{Wa} [dB]	111	111	111
Vibration level, 3 axis [m/s ²]	10.7	10.7	10.7

ACCESSORIES

Dust suppression kit, item no. 3030051. HYCON water container item no. 1113286.

THE HYCON PRODUCT RANGE

CUT-OFF AND RING SAWS · CORE DRILLS · POST DRIVERS · PICK HAMMER · LIGHT & HEAVY DUTY BREAKERS
SUBMERSIBLE PUMPS · ROCK DRILLS · UNDERWATER EQUIPMENT · GASOLINE, DIESEL AND ELECTRIC POWER PACKS



HYCON A/S
Juelstrupparken 11
DK-9530 Støvring

Tel.: +45 9647 5200
Mail: hycon@hycontools.com
www.hycontools.com

DISTRIBUTOR: